

PINNACLE EXO ANSI

MULTI-IMPACT RATED & VENTILATED HELMET WITH EPS



ZPEA01

The Pinnacle Exo is a multi-impact tested helmet with excellent ventilation, providing airflow through the helmet to keep you fresh & comfortable where warm & humid environments are a concern. Ideal for building & civil construction, treecare, work at heights and scaffolding industries & busy worksites.

Manufactured in Italy, the stylish & versatile design of the helmet enables multiple configurations of head, vision, face & hearing protection. Pinnacle Visors fit directly to the helmet. Integrated Euro slots for hearing protection & face visor assemblies.

Lightweight construction and padded inner linings provide unrivalled comfort, with mesh covers over ventilation holes to prevent debris entry into the helmet. The EXO is resistant to molten metal splash and lateral deformation.

CERTIFICATION;

ANSI/ISEA Z89.1-2014, Type I, Class C

EN12492:2012; All parts including;

PR4.2.1 (Shock absorption), PR4.1.3 (Chinstrap Retention System) PR4.2.3.(Chinstrap Retention System Strength <500N)

EN 397:2012+ A1:2012;

LD, MM, -40°C to +50°C. Resistance to lateral deformation (LD); Protection against molten metal splashes (MM); Protection against impacts at low temperatures (-40°C); Protection against impacts at high temperatures (+50°C)



RATING: to CE, -40°C / +50°C
ANSI, -18°C / +49°C

LIFESPAN: Up to 10 Years

MODEL	REF	WEIGHT (G)	SIZE	MATERIAL	APPLICATIONS	CE
ZPE01ANSI	Multi impact helmet with ventilation. ANSI Type 1, Class C	450g	54 – 62cm 21.3 – 24.8 in	Exterior Shell ABS plastic, Interior EPS		

PRODUCT FEATURES

- ABS Advanced Thermo Material Shell exterior.
- Vented helmet provides airflow to keep wearer cool & comfortable
- Optional Pinnacle Visors and Arc Flash Shields are available in several styles for added eye and face protection.
- 10 year lifespan, 2 year warranty
- PPE category: Type 1, Class C
- Inside protection in high-density EPS polystyrene.
- Lightweight and comfortable, just 450gms.
- Dielectric with no metal parts.
- Front & crown paddings absorbs moisture for breathability and are easily removable for washing.
- Attachment loop on chinstrap provided for clipping the helmet to a harness.
- Adjustable retention-type chinstrap, will not release under force of F>500N.
- Headlamp clips are compatible with all headlights with elastic straps.
- One size fits most including larger heads, with quick wheel up/down adjustable size system, Diameter: 54 – 62cm, 21.3 – 24.4 in.
- Made in Italy.
- Hearing protection kits available on request.
- Integrated Euro attachment system for hearing protection and full hearing/face protection configurations such as forestry
- Recommended Accessories; Hellberg, Sordin, Princeton Tec & Paulson

ZERO HEIGHT SAFETY LIMITED

AUSTRALASIA
10 Holt Place,
Harewood, Christchurch 8053
New Zealand
sales.nz@zeroheightsafety.com

EUROPE & UK
Badenerstrasse 122
5466 Kaiserstuhl,
Switzerland
sales.eu@zeroheightsafety.com

